

WITH ROTATION SELECTION AND DRIVE BELT.



<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	32 mm
<b>Face milling cutter max</b>	80 mm
<b>End milling cutter max</b>	20 mm
<b>Spindle taper</b>	CM 3
<b>Chuck sizes</b>	1 - 13 mm B16
<b>Spindle speed</b>	100 - 2080 rpm
<b>Spindle travel</b>	130 mm
<b>Spindle rotation</b>	Dx - Sx
<b>Column</b>	115 mm
<b>Quill</b>	75 mm
<b>Headstock travel</b>	405 mm
<b>Manual vertical feed division</b>	0,05 mm
<b>Distance spindle axis - column surface</b>	197 mm
<b>Distance between spindle nose and table</b>	600 mm
<b>Table dimensions</b>	585 x 190 mm
<b>Slot</b>	12 mm
<b>Longitudinal axis</b>	180 mm
<b>Cross axis</b>	380 mm
<b>Base dimensions</b>	470 x 670 mm
<b>Motor</b>	400 V 50 Hz 1,5 kW
<b>Cooling pump</b>	400v 50 Hz 0.4 KW
<b>Dimensions</b>	928 x 910 x 1700h mm
<b>Net weight</b>	300 kg

**Included**

Drill chuck with key 1 - 13 B16  
Spindle drilled MT 3 B16  
Spindle taper shank MT 3 Ø 27 mm  
Reduction sleeve MT 3/2  
Coolant system  
Oilers  
Tie rod M12  
Service keys

**Packaging dimensions**

960x760x1870 h mm

**Gross weight**

310,00 kg

**EAN Code**

8012667309732