

REVERSIBLE, TILTING HEAD AND TIMED TAPPING, ROTATING TABLE



Max drilling capacity on cast iron with pre-drilling hole	Ø 40 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	Ø 35 mm
Continuous drilling capacity	Ø 30 mm
Tapping capacity	22 mm
Spindle taper	CM 4
Chuck sizes	1 - 16 B16
Spindle speed	(12) 75 - 3200 rpm
Spindle travel	120 mm
Spindle rotation	Dx - Sx
Head tilt left and right	±60°
Quill	Ø 76 mm
Column	Ø 115 mm
Distance between spindle axis and column	297 mm
Distance between spindle nose and table	715 mm
Distance between spindle nose and base	1180 mm
Table dimensions	500 x 460 mm
Slot	14 mm
Base dimensions	650 x 450 x 80 mm
Motor	400 V 50 Hz 1,1/1,5 kW
Dimensions	700 x 480 x 1820 mm
Net weight	330 kg
Packaging dimensions	725 x 760 x 1890 mm
Gross weight	310,00 kg

Included

Keyless chuck 1 - 16 B16
Drill chuck shank MT 4
Reduction sleeve MT 4/3
Reduction sleeve MT 3/2

