


REVERSIBLE, TILTING HEAD, COOLING SYSTEM, TIMED TAPPING AND AUTOMATIC DOWN FEED, ROTATING TABLE.



Max drilling capacity on cast iron with pre-drilling hole	Ø 40 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	Ø 35 mm
Continuous drilling capacity	Ø 30 mm
Tapping capacity	22 mm
Spindle taper	MT 4
Chuck sizes	1 - 16 B16
Spindle speed	(12) 75 - 3200 rpm
Spindle travel	120 mm
Spindle rotation	Dx - Sx
Head tilt left and right	±60°
Quill	Ø 76 mm
Column	Ø 115 mm
Feed range	(3) 0,1 - 0,18 - 0,26 mm/rev
Distance between spindle axis and column	297 mm
Distance between spindle nose and table	715 mm
Distance between spindle nose and base	1180 mm
Table dimensions	500 x 460 mm
Slot	14 mm
Base dimensions	470 x 670 mm
Motor	400 V 50 Hz 1,1/1,5 kW
Dimensions	700 x 480 x 1850 mm
Net weight	340 kg
Packaging dimensions	760x730x1890 h mm

Included

Keyless chuck 1 - 16 B16
Drill chuck shank MT 4
Reduction sleeve MT 4/3
Reduction sleeve MT 3/2

Gross weight

327,00 kg

EAN Code

8012667346188