

REVERSIBLE, TABLE REVERSIBLE WITH 145MM VICE, EQUIPPED WITH LIGHT.



<b>Max drilling capacity on cast iron with pre-drilling hole</b>	Ø 40 mm
<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	Ø 35 mm
<b>Continuous drilling capacity</b>	Ø 30 mm
<b>Spindle taper</b>	MT 4
<b>Chuck sizes</b>	1 - 16 mm B18
<b>Spindle speed</b>	(12) 75 - 3200 rpm
<b>Spindle travel</b>	125 mm
<b>Spindle rotation</b>	Dx - Sx
<b>Quill</b>	Ø 75 mm
<b>Column</b>	Ø 125 mm
<b>Distance between spindle axis and column</b>	320 mm
<b>Distance between spindle nose and table</b>	80 - 680 mm
<b>Distance between spindle nose and base</b>	1140 mm
<b>Table dimensions</b>	500 x 380 mm
<b>Slot</b>	14 mm
<b>Tilting table</b>	±90°
<b>Vice</b>	125 mm
<b>Base dimensions</b>	460 x 650 mm
<b>Motor</b>	400 V 50 Hz 1,1/1,5 kW
<b>Dimensions</b>	500 x 750 x 2000 mm
<b>Net weight</b>	350 kg
<b>Packaging dimensions</b>	800x570x2090 h mm
<b>Gross weight</b>	367,00 kg

**Included**

Drill chuck with key 1 - 16 mm B18  
Spindle drilled MT 4 B18  
Reduction sleeve MT 4/3  
Reduction sleeve MT 3/2

