

WITH AUTOFEED, COOLANT SYSTEM, PARTIALLY ROTATING TABLE,  
WITH 125MM VICE.



<b>Max drilling capacity on cast iron with pre-drilling hole</b>	Ø 31,75 mm
<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	Ø 31,75 mm
<b>Continuous drilling capacity</b>	Ø 25 mm
<b>Spindle taper</b>	MT 3
<b>Chuck sizes</b>	1 - 16 B18
<b>Spindle speed</b>	(8) 160 - 2200 rpm
<b>Spindle travel</b>	130 mm
<b>Column</b>	Ø 115 mm
<b>Feed range</b>	0,1- 0,16- 0,26 mm/rev
<b>Distance between spindle axis and column</b>	223 mm
<b>Distance between spindle nose and table</b>	696 mm
<b>Distance between spindle nose and base</b>	1135 mm
<b>Table dimensions</b>	400 x 470 mm
<b>Travel of table</b>	510 mm
<b>Slot</b>	14 mm
<b>Base dimensions</b>	400 x 310 mm
<b>Motor</b>	400 V 50 Hz 0,85 kW / 1,1 kW
<b>Cooling pump</b>	400 V 50 Hz 40 W
<b>Overall sizes</b>	900 x 545 x 1765 mm
<b>Net weight</b>	340 kg
<b>Packaging dimensions</b>	950 x 570 x 1920 h mm
<b>Gross weight</b>	360,50 kg
<b>EAN Code</b>	8012667226855

**Included**

Drill chuck with key 1 - 16 B18  
Spindle drilled MT 3  
Reduction sleeve MT 3/2