

ROTATING AND INCLINABLE TABLE. ELECTRICAL SYSTEM WITH SEPARATE 24V CIRCUIT FOR ON-BOARD MACHINE CONTROLS.



<b>Max drilling capacity on cast iron with pre-drilling hole</b>	Ø 25 mm
<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	Ø 20 mm
<b>Continuous drilling capacity</b>	Ø 16 mm
<b>Spindle taper</b>	CM 2
<b>Chuck sizes</b>	1 - 16 mm B18
<b>Spindle speed</b>	(16) 220 - 2840 rpm
<b>Spindle travel</b>	80 mm
<b>Quill</b>	Ø 47 mm
<b>Column</b>	Ø 80 mm
<b>Height</b>	990 mm
<b>Distance spindle axis - column surface</b>	175 mm
<b>Distance between spindle nose and table</b>	420 mm
<b>Distance between spindle nose and base</b>	600 mm
<b>Table dimensions</b>	290 x 290 mm
<b>Slot</b>	14 mm
<b>Tilting table</b>	± 45°
<b>Turning table</b>	Yes
<b>Base dimensions</b>	460 x 275 mm
<b>Motor</b>	230 V 50 Hz 0,75 kW
<b>Dimensions</b>	300 X 630 X 990h mm
<b>Net weight</b>	57 kg
<b>Packaging dimensions</b>	900x570x335 h mm
<b>Gross weight</b>	61,50 kg

**Included**

Keyless chuck 1 - 16 B18  
Drill chuck shank MT 2  
Cones remover  
Allen keys

