


SE UTILIZA PRINCIPALMENTE EN TORNOS CON EL OBJETIVO DE ESTABILIZAR PIEZAS LARGAS Y DELGADAS, MÁS SUJETAS A FLEXIONES U...



€213,00



Cono mordazas

A	3	L2 48 mm - D2-D3 20 mm - $\hat{I}\pm 60^\circ$ mm
B		L2 43,5 mm - D2-D3 20 mm - $\hat{I}\pm 75^\circ$ mm
C		L2 40,5 mm - D2-D3 20 mm - $\hat{I}\pm 90^\circ$ mm
D		L2 56 mm - D2-D3 18 mm - $\hat{I}\pm 60^\circ$ mm
E		L2 50 mm - D2-D3 35 mm / 15 mm - $\hat{I}\pm 60^\circ$ mm
F		L2 42 mm - D2-D3 22 mm / 18 mm - $\hat{I}\pm 60^\circ$ mm
G		L2 48 mm - D2-D3 35 mm / 30 mm - $\hat{I}\pm 60^\circ$ mm

Máx. r.p.m. 5000 g/min

Capacidad máx. 150 kg

Peso bruto 2,18 kg

Codigo de barras 8012667205201



Estuche de transporte



Templado



9 Pcs



Acero



Rectificado